

Two-channel safety barriers

Series 9002

INTRINSPAK



A2



04101E00

- Wide product range for all standard applications of the automation
- Flexible and space-saving – available in single and double channel versions
- Time-saving installation thanks to simultaneous
 - snap-on mounting on rails and
 - connection to PE and earth
- Reduced stock-keeping thanks to a uniform back-up fuse



The R. STAHL INTRINSPAK safety barriers of Series 9002 can be used for various tasks in the field of automation. The wide product range and scope of different combinations offer you a large field of applications.

The safety barriers allow the intrinsically safe operation of HART transmitters, proximity sensors, potential-free contacts, temperature sensors, DMS, solenoid valves, indicators and others. Due to the compact width, space-saving and flexible installation in the switch cabinet is possible. Thanks to DIN-rail mounting and simultaneous connection of the equipotential bonding, the installation can be performed very easily.

	ATEX / IECEx						Zone	NEC 505	NEC 506				Division	NEC 500							
	0	1	2	20	21	22			Class I	0	1	2	20	21	22	Class I	Class II	Class III			
Ex i interface	x	x	x	x	x	x	Ex i interface								Ex i interface	x	x	x	x	x	x
Installation in		x			x		Installation in		x			x			Installation in	x	x	x		x	x

WebCode 9002A

Two-channel safety barriers

Series 9002



Explosion Protection

Global (IECEx)

Gas and dust	IECEx PTB 08.0057X Ex nA [ia Ga] IIC T4 Gc [Ex ia Da] IIIC
--------------	--

Europe (ATEX)

Gas and dust	PTB 01 ATEX 2053 X Ex II 3 (1) G Ex nA [ia Ga] IIC/IIB T4 Gc Ex II (1) D [Ex ia Da] IIIC
--------------	--

Certificates

Certificates	IECEx, ATEX, Brasil (INMETRO), Canada (CSA), Kazakhstan (TR), Korea (KCs), Russia (TR), Serbia (SRPS), Ukraine (TR), USA (FM, UL), Belarus (TR)
--------------	---

Further parameters

Installation	in Zone 2, Division 2 and in safe area
Further information	see respective certificate and operating instructions

Technical Data

Electrical data

Transmission characteristic	
Leakage current at U_N	$\leq 2 \mu\text{A}$ (unless specified otherwise)
Temperature influence	$\leq 0.25 \% / 10 \text{ K}$
Transmission frequency	
In case of resistive current limiting	
$I_m \leq 50 \text{ mA}$	$\leq 50 \text{ kHz}$
$I_m \geq 50 \text{ mA}$	$\leq 100 \text{ kHz}$
In case of electronic current limiting	$\leq 10 \text{ kHz}$


Ambient conditions

Ambient temperature	-20 ... +60 °C
Storage temperature	-20 ... +75 °C
Maximum relative humidity	95 % on average, no condensation

Mechanical data

Degree of protection	according to IEC 60529
Terminal support	IP20
Enclosure	IP40
Enclosure material	polyamide 6GF
Connection type	4 connection terminals (cage terminals), each maximum 1.5 mm ² finely stranded / solid wire 2 PA-terminals, each maximum 4 mm ² finely stranded / solid
Weight	approx 0.115 kg

Two-channel safety barriers, potential: + / +



- Connection to regulated power supply U_N
- Installation permitted in Division 2 and Zone 2

05820E01

A2

Selection table

Channel	U_N	R_{min}	R_{max}	I_{max}	Safety data						Order number	
					U_o	I_o	P_o	IIC		IIB		
V	Ω	Ω	mA	V	mA	mW	mH	μF	mH	μF		
1	9	1043	1156	7.7	12	12	40	240	1.41	850	9	9002/11-120-024-001
2	9	1043	1156	7.7	12	12	40	240	1.41	850	9	9002/11-130-360-001
1+2	--	--	--	--	12	24	70	63	1.1	230	7.1	
1	10	45	52	100	13	321	1040	0.19	1	1.6	6	9002/11-130-360-001 *)
2	1	45	52	19	1.6	39	16	24	100	91	100	
1+2	--	--	--	--	13	360	1170	0.17	0.79	1.3	5	
1	10	953	978	10	13.7	14.5	50	160	0.79	560	5	9002/11-137-029-001
2	10	953	978	10	13.7	14.5	50	160	0.79	560	5	
1+2	--	--	--	--	13.7	29	100	43	0.67	160	4.18	
1	16	1423	1576	10	19.9	15	75	160	0.223	560	1.42	9002/11-199-030-001
2	16	1423	1576	10	19.9	15	75	160	0.223	560	1.42	
1+2	--	--	--	--	19.9	30	150	40	0.223	150	1.42	
1	22.5	321	358	62	26	87	540	2.7	0.099	15.4	0.77	9002/11-260-138-001
2	17.5	416	463	37	20	51	245	14	0.22	54	1.41	
1+2	--	--	--	--	26	138	785	0.81	0.087	5.1	0.67	
1	25	321	358	69	28	93	650	2	0.083	13	0.65	9002/11-280-186-001
2	25	321	358	69	28	93	650	2	0.083	13	0.65	
1+2	--	--	--	--	28	186	1300	--	--	2.8	0.551	
1	25	321	358	69	28	89	630	2.2	0.083	14	0.65	9002/11-280-293-001
2	6	59	68	88	9.6	180	430	0.6	3.6	5	26	
1+2	--	--	--	--	28	269	1050	--	--	0.56	0.62	

*) max. leakage current $I_{leak} \leq 10 \mu A$

Functional data and safety-relevant maximum values

U_N	Nominal voltage	I_{max}	Maximum output current	P_o	Maximum power
R_{min}	Minimum resistance of the safety barrier	U_o	Maximum voltage	L_o	max. permissible external inductance
R_{max}	Maximum resistance of the safety barrier	I_o	Maximum current	C_o	max. permissible external capacity

Two-channel safety barriers, potential: + / +


Series 9002/11



Application case

Load cell (DMS) 350 Ω or 700 Ω
6 conductors + 16 V, field circuit unearthing

Schematic



Operating data

Operating voltage
Voltage for load cell and electric line
Current for load cell

$$U_N \leq +16 \text{ V}$$

$$U_L (\text{at } U_N = +16 \text{ V})$$

$$I_L (\text{at } U_N = +16 \text{ V})$$

Number of the load cells connected in parallel	350 Ω		700 Ω	
	U_L (V)	I_{mA} (V)	U_L (V)	I_{mA} (V)
1	10.4	30	12.1	17
2	8.3	47	10.4	30
3	6.9	60	9.5	41
4	5.9	67	8.3	47

Safety data

Maximum voltage
Maximum current
Maximum permissible external inductance
Maximum permissible external capacity
Maximum power

$$U_o = 19.9 \text{ V}$$

$$I_o = 285 \text{ mA}$$

IIC IIB

$$L_o \quad 0.2 \text{ mH}$$

$$1.8 \text{ mH}$$

IIC IIB

$$C_o \quad 0.223 \mu\text{F}$$


$$1.42 \mu\text{F}$$

$$P_o = 1.42 \text{ W}$$

Application note
For 4-wire circuits (without sense) the respective safety barrier might be unnecessary. The operating data remains unchanged. The safety-relevant maximum current is reduced to $I_o = 255 \text{ mA}$, the maximum power to $P_o = 1.3 \text{ W}$.


3-wire NPN inputs (negative switching) of proximity switches, photocells and encoders

Schematic




Discrete 2-wire output for solenoid valves, LEDs and signalling devices

Schematic



Two-channel safety barriers, potential: + / +



- Application for 3-wire NPN, sensors with voltage output
- Low nominal current
- Installation permitted in Division 2 and Zone 2

A2

Selection table

Channel	UN	R _{min}	R _{max}	I _{max}	Safety data						Order number	
					IIC		IIB					
					U _o	I _o	P _o	L _o	C _o	L _o	C _o	
V	Ω	Ω	mA	V	mA	mW	mH	μF	mH	μF	μF	
1	24	264	296	91	28	109	760	1.3	0.083	9	0.65	9002/11-280-112-001
2	24	11979	12221	2	28	3	20	50	0.083	150	0.65	
1+2	--	--	--	--	28	112	780	0.76	0.065	84	0.551	


Functional data and safety-relevant maximum values

U _N	Nominal voltage	I _{max}	Maximum output current	P _o	Maximum power
R _{min}	Minimum resistance of the safety barrier	U _o	Maximum voltage	L _o	max. permissible external inductance
R _{max}	Maximum resistance of the safety barrier	I _o	Maximum current	C _o	max. permissible external capacity

Application case

3-wire NPN inputs (negative switching) of proximity switches, photocells and encoders

Schematic



Application note


With this barrier all loop voltages must be checked to ensure correct function.

Two-channel safety barriers, potential: + / +

Series 9002/11



Two-channel safety barriers, potential: + / +



Selection table

Channel	U _N	R _{min}	R _{max}	I _{max}	Safety data						Order number	
					U _o	I _o	P _o	IIC		IIB		
	V	Ω	Ω	mA	V	mA	mW	mH	μF	mH	μF	
1	25	321	358	69	28	89	630	2.2	0.083	14	0.65	9002/11-280-293-021
2	6	59	68	88	9.6	180	430	0.6	3.6	5	26	
1+2	--	--	--	--	28	269	1050	--	--	0.56	0.62	


Functional data and safety-relevant maximum values

U _N	Nominal voltage	I _{max}	Maximum output current	P _o	Maximum power
R _{min}	Minimum resistance of the safety barrier	U _o	Maximum voltage	L _o	max. permissible external inductance
R _{max}	Maximum resistance of the safety barrier	I _o	Maximum current	C _o	max. permissible external capacity

Application case

2-wire, 4/20 mA transmitters - standard and HART


Schematic



Application note

This safety barrier is used if the automation system only accepts signals from 1 to 5 V. This barrier contains a 250 Ω resistor to convert the signal 1 ... 5 V.

Two-channel safety barriers, potential: - / -



A2

Selection table

Channel	U_N	R_{min}	R_{max}	I_{max}	Safety data						Order number	
					U_o	I_o	P_o	IIC		IIB		
	V	Ω	Ω	mA	V	mA	mW	L_o	C_o	L_o	C_o	
1	9	1043	1156	7.7	12	12	40	240	1.41	850	9	9002/00-120-024-001
2	9	1043	1156	7.7	12	12	40	240	1.41	850	9	
1+2	--	--	--	--	12	24	70	63	1.1	230	7.1	
1	22.5	321	358	62	26	87	540	2.7	0.099	15.4	0.77	9002/00-260-138-001
2	17.5	416	463	37	20	51	245	14	0.22	54	1.41	
1+2	--	--	--	--	26	138	785	0.81	0.087	5.1	0.67	
1	25	321	358	69	28	93	650	2	0.083	13	0.65	9002/00-280-186-001
2	25	321	358	69	28	93	650	2	0.083	13	0.65	
1+2	--	--	--	--	28	186	1300	--	--	2.8	0.551	


Functional data and safety-relevant maximum values

U_N	Nominal voltage	I_{max}	Maximum output current	P_o	Maximum power
R_{min}	Minimum resistance of the safety barrier	U_o	Maximum voltage	L_o	max. permissible external inductance
R_{max}	Maximum resistance of the safety barrier	I_o	Maximum current	C_o	max. permissible external capacity

Application case

Vibration sensor

Schematic



Operating data

Operating voltage $U_N = -24V$
Series resistance of the safety barrier $R = 358 \Omega$

Safety data

Maximum voltage	$U_o = 26 V$	
Maximum current	$I_o = 138 mA$	
Maximum permissible external inductance	$L_o = 0.81 mH$	IIC
Maximum permissible external capacity	$C_o = 0.087 \mu F$	IIB
Maximum power	$P_o = 850 mW$	


Application note
Application of the barrier for Bentley Nevada and Metrix position transducer. This barrier has negative potential; for a positive potential, use the barrier 9002/11-260-138-001.

Two-channel safety barriers, potential: + / -

Series 9002/10



Two-channel safety barriers, potential: + / -



Selection table

Channel	U _N	R _{min}	R _{max}	I _{max}	Safety data						Order number	
					U _o	I _o	P _o	IIC		IIB		
	V	Ω	Ω	mA	V	mA	mW	mH	μF	mH	μF	
1 2 1+2	6	490	543	11	9.33	20	50	90	3.9	330	29	9002/10-187-020-001
	6	490	543	11	9.33	20	50	90	3.9	330	29	
	--	--	--	--	18.7	20	90	90	0.27	330	1.64	
1 2 1+2	6	42	49	122	9.33	270	630	0.23	3.9	2.2	29	9002/10-187-270-001
	6	42	49	122	9.33	270	630	0.23	3.9	2.2	29	
	--	--	--	--	18.7	270	1260	0.23	0.27	2.2	1.64	


Functional data and safety-relevant maximum values

U _N	Nominal voltage	I _{max}	Maximum output current	P _o	Maximum power
R _{min}	Minimum resistance of the safety barrier	U _o	Maximum voltage	L _o	max. permissible external inductance
R _{max}	Maximum resistance of the safety barrier	I _o	Maximum current	C _o	max. permissible external capacity

Application case

Load cell (DMS) 350 Ω or 700 Ω
6 conductors +/- 7.5 V (15 V), field circuit unearthing

Schematic



09962E01

A2

Operating data

Operating voltage
Voltage for load cell and electric line
Current for load cell

$$U_N \leq \pm 7.5 \text{ V (15 V)}$$

$$U_L (\text{at } U_N \leq \pm 7.5 \text{ V})$$

$$I_L (\text{at } U_N \leq \pm 7.5 \text{ V})$$

Number of the load cells connected in parallel	350 Ω		700 Ω	
	U_L (V)	I_{mA} (V)	U_L (V)	I_{mA} (V)
1	11.6	35	13.2	19
2	9.6	55	11.6	35
3	8	70	10.6	45
4	7	80	9.6	55

Safety data

Maximum voltage
Maximum current
Maximum permissible external inductance
Maximum permissible external capacity
Maximum power

$$U_o = 18.7 \text{ V}$$

$$I_o = 330 \text{ mA}$$

L_o	IIC 0.18 mH	IIB 1.45 mH
C_o	IIC 0.27 μF	IIB 1.64 μF

$$P_o = 1.45 \text{ W}$$


For 4-wire circuits (without sense) the respective safety barrier might be unnecessary. The operating data remains unchanged. The safety-relevant maximum current is reduced to $I_o = 310 \text{ mA}$, the maximum power to $P_o = 1.36 \text{ W}$.

Two-channel safety barriers, potential: ~ / ~

Series 9002/22



Two-channel safety barriers, potential: ~ / ~



Selection table

Channel	U_N	R_{min}	R_{max}	I_{max}	Safety data						Order number	
					U_o	I_o	P_o	IIC		IIB		
	V	Ω	Ω	mA	V	mA	mW	mH	μF	mH	μF	
1	0.7	19.9	20.1	33	1.6	150	60	1.3	100	7	1000	9002/22-032-300-111 *)
2	0.7	19.9	20.1	33	1.6	150	60	1.3	100	7	1000	
1+2	1.4	--	--	--	3.2	300	120	0.2	100	1.8	1000	

*) max. leakage current $I_{leak} \leq 10 \mu A$


Functional data and safety-relevant maximum values

U_N	Nominal voltage	I_{max}	Maximum output current	P_o	Maximum power
R_{min}	Minimum resistance of the safety barrier	U_o	Maximum voltage	L_o	max. permissible external inductance
R_{max}	Maximum resistance of the safety barrier	I_o	Maximum current	C_o	max. permissible external capacity

Application case

Pt100, 2-wire circuit, field circuit unearthing

Schematic



09959E01

Operating data


Operating voltage	$U_N \leq 1.4 \text{ V}$
Series resistance of the safety barrier	$R = 2 \times (20 \Omega \pm 0.1 \Omega)$
Measuring range	$\leq 400 \text{ }^{\circ}\text{C} (I_N \leq 5 \text{ mA})$ $\leq 850 \text{ }^{\circ}\text{C} (I_N \leq 3 \text{ mA})$

Safety data

Maximum voltage	$U_o = 3.2 \text{ V}$
Maximum current	$I_o = 300 \text{ mA}$
Maximum permissible external inductance	L_o IIC 0.2 mH IIB 1.8 mH
Maximum permissible external capacity	C_o IIC 100 μF IIB 1000 μF

Pt100, 3-wire circuit, field circuit unearthing

Schematic



09960E01

Operating data

Operating voltage	$U_N \leq 1.4 \text{ V}$
Series resistance of the safety barrier	$R = 2 \times (20 \Omega \pm 0.1 \Omega)$
Measuring range	$\leq 400 \text{ }^{\circ}\text{C} (I_N \leq 5 \text{ mA})$ $\leq 850 \text{ }^{\circ}\text{C} (I_N \leq 3 \text{ mA})$

Safety data

Maximum voltage	$U_o = 3.2 \text{ V}$
Maximum current	$I_o = 450 \text{ mA}$
Maximum permissible external inductance	L_o IIC 0.12 mH IIB 0.5 mH
Maximum permissible external capacity	C_o IIC 100 μF IIB 1000 μF


A2

Two-channel safety barriers, potential: ~ / ~

Series 9002/22



Two-channel safety barriers, potential: ~ / ~



Selection table

Channel	U_N	R_{min}	R_{max}	I_{max}	Safety data						Order number	
					U_o	I_o	P_o	IIC		IIB		
	V	Ω	Ω	mA	V	mA	mW	mH	μF	L_o	C_o	
1	5.5	84	95	57	7.9	100	198	4	8.8	15	115	9002/22-158-200-001
2	5.5	84	95	57	7.9	100	198	4	8.8	15	115	
1+2	11	--	--	--	15.8	200	395	0.5	0.478	4	2.88	
1	9	1043	1156	7.7	12	12	40	240	1.41	850	9	9002/22-240-024-001
2	9	1043	1156	7.7	12	12	40	240	1.41	850	9	
1+2	18	--	--	--	24	24	80	41	0.125	145	0.93	
1	9	158	177	50	12	80	240	6	1.41	22	9	9002/22-240-160-001
2	9	158	177	50	12	80	240	6	1.41	22	9	
1+2	18	--	--	--	24	160	480	0.7	0.125	4	0.93	


Functional data and safety-relevant maximum values

U_N	Nominal voltage	I_{max}	Maximum output current	P_o	Maximum power
R_{min}	Minimum resistance of the safety barrier	U_o	Maximum voltage	L_o	max. permissible external inductance
R_{max}	Maximum resistance of the safety barrier	I_o	Maximum current	C_o	max. permissible external capacity


Application case

with RS 232

Schematic



Two-channel safety barriers, safety barrier potential: + / evaluation barrier potential: +



- Function:
Channel 1 current supply
Channel 2 evaluation barrier
No safety-relevant output current I_o for channel 2
- Nominal current limited to 40 mA at 250 Ω load
- Connection to unregulated power supply on U_N to channel 1
- Installation permitted in Division 2 and Zone 2

05439E02

Selection table

Channel	U_N	R_{min}	R_{max}	I_{max}	ΔU	Safety data						Order number		
						U_o	I_o	P_o	IIC		IIB			
						V	Ω	Ω	mA	V	mA	mW	mH	μF
1	20 - 35	216	243	86	--	25.2	118	740	1.3	0.107	7.4	0.82	9002/13-252-121-041	*
2	22	--	--	--	3.5	25.2	0	20	50	0.107	150	0.82		
1+2	--	--	--	--	--	25.2	121	760	1.25	0.104	7.35	0.8		

*) only for channel 1: leakage current at 24 V / 35 V $I_{leak} \leq 1 \text{ mA} / 10 \text{ mA}$


Functional data and safety-relevant maximum values

U_N	Nominal voltage	ΔU	Additional voltage drop across the safety barrier	L_o	max. permissible external inductance
R_{min}	Minimum resistance of the safety barrier	U_o	Maximum voltage	C_o	max. permissible external capacity
R_{max}	Maximum resistance of the safety barrier	I_o	Maximum current		
I_{max}	Maximum output current	P_o	Maximum power		

Application case

Analog output (current source) for I/P converter etc., field circuit unearthed

Schematic



09953E01

Operating data


Operating voltage	$U_N = + 20 \dots 35 \text{ V}$
Operating current	$I_N = 0 \dots 22 \text{ mA}$
Maximum voltage drop at the safety barrier	$\Delta U_{\max} (8.9 \text{ V})$

Safety data

Maximum voltage	$U_o = 25.2 \text{ V}$	
Maximum current	$I_o = 121 \text{ mA}$	
Maximum permissible external inductance	L_o IIC IIB 1.25 mH 7.35 mH	
Maximum permissible external capacity	C_o IIC IIB 0.104 μF 0.8 μF	
Maximum power	$P_o = 763 \text{ mW}$	

Analog output (current source) for I/P converter etc., field circuit unearthed

Schematic



06604E01

Operating data


Operating voltage	$U_N = + 20 \dots 35 \text{ V}$	
Open-circuit output voltage (terminal 3 4, $I_n = 0$)	U_L $U_N (24 \text{ V})$ $U_N > 24 \text{ V}$ $U_N - 3.5 \text{ V}$ 21 V	
Operating current	$I_N = U_L / 243 \Omega + R_L$	

Safety data

Maximum voltage	$U_o = 25.2 \text{ V}$	
Maximum current	$I_o = 121 \text{ mA}$	
Maximum permissible external inductance	L_o IIC IIB 1.25 mH 7.35 mH	
Maximum permissible external capacity	C_o IIC IIB 0.104 μF 0.8 μF	
Maximum power	$P_o = 760 \text{ mW}$	

Application note
 This safety barrier is used if the automation system activates the analog output signal in the return (negative) line. The field device and automation system are not earthed and unregulated power supply can be used.

Two-channel safety barriers, safety barrier potential: + / evaluation barrier potential: +



Selection table

Channel	U_N	R_{min}	R_{max}	I_{max}	ΔU	Safety data						Order number	
						IIC		IIB					
						U_o	I_o	P_o	L_o	C_o	L_o	C_o	
V	Ω	Ω	mA	V	V	mA	mA	mW	mH	μF	mH	μF	
1	16	95	108	148	--	19.9	222	1100	0.39	0.223	3.18	1.42	9002/13-199-225-001 *)
2	16	--	--	--	2	19.9	3	15	1000	0.223	1000	1.42	
1+2	--	--	--	--	--	19.9	225	1120	0.37	0.213	3.15	1.38	
1	24	321	358	67	--	28	90	630	2.2	0.083	14	0.65	9002/13-280-093-001
2	24	--	--	--	2	28	3	21	50	0.083	150	0.65	
1+2	--	--	--	--	--	28	93	651	2	0.08	13	0.636	
1	24	269	290	82	--	28	107	749	1.35	0.083	9.6	0.65	9002/13-280-110-001
2	24	--	--	--	2	28	3	21	50	0.083	150	0.65	
1+2	--	--	--	--	--	28	110	770	1.25	0.08	9	0.635	

*) only for channel 2: max. leakage current $I_{leak} \leq 10 \mu A$


Functional data and safety-relevant maximum values

U_N	Nominal voltage	ΔU	Additional voltage drop across the safety barrier	L_o	max. permissible external inductance
R_{min}	Minimum resistance of the safety barrier	U_o	Maximum voltage	C_o	max. permissible external capacity
R_{max}	Maximum resistance of the safety barrier	I_o	Maximum current		
I_{max}	Maximum output current	P_o	Maximum power		

Application case

Load cell (DMS) 350 Ω or 700 Ω
 6 conductors + 16 V, field circuit unearthed

Schematic



Operating data

Operating voltage $U_N \leq +16 \text{ V}$

Voltage for load cell and electric line $U_L (\text{at } U_N = +16 \text{ V})$

Current for load cell $I_L (\text{at } U_N = +16 \text{ V})$

Number of the load cells connected in parallel	350 Ω		700 Ω	
	$U_L (\text{V})$	$I_{mA} (\text{V})$	$U_L (\text{V})$	$I_{mA} (\text{V})$
1	10.4	30	12.1	17
2	8.3	47	10.4	30
3	6.9	60	9.5	41
4	5.9	67	8.3	47

Safety data

Maximum voltage $U_o = 19.9 \text{ V}$

Maximum current $I_o = 285 \text{ mA}$

Maximum permissible external inductance L_o IIC 0.2 mH IIB 1.8 mH


Maximum permissible external capacity C_o IIC IIB 0.223 μF 1.42 μF

Maximum power $P_o = 1.42 \text{ W}$

Application note For 4-wire circuits (without sense) the respective safety barrier might be unnecessary. The operating data remains unchanged. The safety-relevant maximum current is reduced to $I_o = 255 \text{ mA}$, the maximum power to $P_o = 1.3 \text{ W}$.

Discrete 2-wire output for solenoid valves, LEDs and signalling devices

Schematic




Application note

This barrier is suitable for use with regulated power supplies and earthed return circuits. The nominal voltage is 24 V.

2-wire 4/20 mA I/P converters and control valves - standard and HART, 4/20 mA indicators


Schematic



Application note

This safety barrier is used if the automation system activates the analog output signal in the return (negative) line. The field device and automation system are not earthed and a regulated power supply must be used. At an operating current of 0 ... 22 mA, the maximum voltage drop across the barrier will be 8.4 V.

Two-channel safety barriers, safety barrier potential: + / evaluation barrier potential: +



- Function:
Channel 1 current supply
Channel 2 evaluation barrier
No safety-relevant output current I_o for channel 2
- Connection to unregulated power supply on U_N to channel 1
- Nominal current limited to 35 mA
- Installation permitted in Division 2 and Zone 2

05827E02

Selection table

Channel	U_N	R_{min}	R_{max}	I_{max}	ΔU	Safety data						Order number	
						IIC		IIB					
						U_o	I_o	P_o	L_o	C_o	L_o	C_o	
V	Ω	Ω	mA	V	V	mA	mW	mH	μF	mH	μF		
1	20 - 35	292	327	35	--	28	97	679	1.8	0.083	12	0.65	9002/13-280-100-041 *)
2	26	--	--	--	3.5	28	0	21	50	0.083	150	0.65	
1+2	--	--	--	--	--	28	100	700	1.55	0.08	11	0.635	

*) only for channel 1: leakage current < 26 V / > 26 V $I_{leak} \leq 1 \text{ mA} / 35 \text{ mA}$


Functional data and safety-relevant maximum values

U_N	Nominal voltage	ΔU	Additional voltage drop across the safety barrier	L_o	max. permissible external inductance
R_{min}	Minimum resistance of the safety barrier	U_o	Maximum voltage	C_o	max. permissible external capacity
R_{max}	Maximum resistance of the safety barrier	I_o	Maximum current		
I_{max}	Maximum output current	P_o	Maximum power		

Application case


3-wire PNP inputs (positive switching) of proximity switches, photocells and encoders

Schematic



06595E02

Two-channel safety barriers, evaluation barrier potential: + / evaluation barrier potential: +



Selection table

Channel	U_N	I_{max}	ΔU	Safety data				Order number	
				U_o	I_o	IIC	IIB		
	V	mA	V	V	mA	L_o	C_o	L_o	C_o
1	25.5	60	3.5 *)	28	0	1000	0.083	1000	0.65
2	25.5	60	3.5 *)	28	0	1000	0.083	1000	0.65
1+2	--	--	--	28	0	1000	0.083	1000	0.65

*) 2.5 V to 20 mA


Functional data and safety-relevant maximum values

U_N	Nominal voltage	U_o	Maximum voltage	C_o	max. permissible external capacity
I_{max}	Maximum output current	I_o	Maximum current		
ΔU	Additional voltage drop across the safety barrier	L_o	max. permissible external inductance		

Application case


Combination of potential-free contacts

Schematic



14682E00

Two-channel safety barriers, evaluation barrier potential: + / evaluation barrier potential: -



- Evaluation barrier for direct current signals with max. output current I_o
 - Application for passive signals of 4/20 mA (transmitter with 4 conductors or more) with insulated analog input on the control system
 - Channel for positive and negative potential in one module
 - Installation permitted in Division 2 and Zone 2

A2

Selection table

Channel	U _N	I _{max}	ΔU	Safety data						Order number	
				IIC		IIB					
				U _o	I _o	L _o	C _o				
	V	mA	V	V	mA	mH	μF	mH	μF		
1	+ 16	100	3.5 *)	28	0	1000	0.22	1000	1.14	9002/34-280-000-001	
2	- 5	100	3.5 *)	8	0	1000	8.4	1000	100		
1+2	21	--	--	28	0	1000	0.083	1000	0.65		

^{*)} 2.5 V to 20 mA


Functional data and safety-relevant maximum values

U_N	Nominal voltage	U_o	Maximum voltage	C_o	max. permissible external capacity
I_{max}	Maximum output current	I_o	Maximum current		
ΔU	Additional voltage drop across the safety barrier	L_o	max. permissible external inductance		

Application case

Transmitter (4-wire)

Schematic



09951E011

Operating data

Operating current	$I_N = 0 \dots 22 \text{ mA}$
Load	$R_L \leq 750 \Omega$
Maximum voltage drop at the safety barrier	$\Delta U_{\max} \leq 3.5 \text{ V}$

Safety data

Maximum voltage	$U_o = 28 \text{ V}$						
Maximum current	$I_o = 0 \text{ mA}$						
Maximum permissible external inductance	The inductance is determined depending on the maximum current of the transmitter						
Maximum permissible external capacity	<table style="width: 100%; border-collapse: collapse;"> <tr> <th style="text-align: left; width: 25%;">C_o</th> <th style="text-align: center; width: 25%;">IIC</th> <th style="text-align: center;">IIB</th> </tr> <tr> <td style="width: 25%;">$0.083 \mu\text{F}$</td> <td style="width: 25%; text-align: center;">$0.65 \mu\text{F}$</td> <td style="width: 25%;"></td> </tr> </table>	C _o	IIC	IIB	$0.083 \mu\text{F}$	$0.65 \mu\text{F}$	
C _o	IIC	IIB					
$0.083 \mu\text{F}$	$0.65 \mu\text{F}$						


A potential-free input is required for the circuit.
If the input is earthed, (R_L to /PA), the safety barrier 9001/03-280-000-001 can be used.

Two-channel safety barriers, star barrier / star barrier

Series 9002/77



Two-channel safety barriers, star barrier / star barrier



Selection table

Channel	U _N	R _{min}	R _{max}	Safety data								Order number	
				U _o		I _o		P _o		IIC			
				V	Ω	Ω	V	mA	mW	mH	μF		
1 2 1+2	6	492	545	9.3	20	50	90	4.1	330	31		9002/77-093-040-001	
		492	545	9.3	20	50	90	4.1	330	31			
		--	--	9.3	40	90	23	4.1	87	31			
1 2 1+2	6	71	82.1	9.3	150	350	1.3	4.1	7	31		9002/77-093-300-001	
		71	82.1	9.3	150	350	1.3	4.1	7	31			
		--	--	9.3	300	700	0.2	4.1	1.8	31			
1 2 1+2	6	60	69.2	10	200	500	0.5	3	4	20.2		9002/77-100-400-001	
		60	69.2	10	200	500	0.5	3	4	20.2			
		--	--	10	400	1000	0.15	3	0.8	20.2			
1 2 1+2	12	111	126	15	150	560	1.3	0.58	7	3.55		9002/77-150-300-001	
		111	126	15	150	560	1.3	0.58	7	3.55			
		--	--	15	300	1130	0.2	0.58	1.8	3.55			
1 2 1+2	18	321	358	22	73	400	7	0.165	26	1.14		9002/77-220-146-001 *)	
		321	358	22	73	400	7	0.165	26	1.14			
		--	--	22	146	800	1.4	0.165	7.4	1.14			
1 2 1+2	18	159	180	22	148	810	1.35	0.165	7.2	1.14		9002/77-220-296-001 *)	
		159	180	22	148	810	1.35	0.165	7.2	1.14			
		--	--	22	296	1630	0.24	0.165	1.84	1.14			
1 2 1+2	24	657	730	28	47	330	10.1	0.083	30	0.65		9002/77-280-094-001	
		657	730	28	47	330	10.1	0.083	30	0.65			
		--	--	28	94	660	1.96	0.083	12.5	0.65			

^{*)} Ambient temperature - 20 + 50 °C.


Functional data and safety-relevant maximum values

U_N	Nominal voltage	U_o	Maximum voltage	L_o	max. permissible external inductance
R_{min}	Minimum resistance of the safety barrier	I_o	Maximum current	C_o	max. permissible external capacity
R_{max}	Maximum resistance of the safety barrier	P_o	Maximum power		

Application case

Load cell (DMS) 350 Ω or 700 Ω
6 conductors +/- 7.5 V (15 V), field circuit unearthing

Schematic



09962E01

Operating data

Operating voltage
Voltage for load cell and electric line
Current for load cell

$U_N \leq \pm 7.5 V$ (15 V)

U_L (at $U_N \leq \pm 7.5 V$)

I_L (at $U_N \leq \pm 7.5 V$)

Number of the load cells connected in parallel	350 Ω		700 Ω	
	U_L (V)	I_{mA} (V)	U_L (V)	I_{mA} (V)
1	11.6	35	13.2	19
2	9.6	55	11.6	35
3	8	70	10.6	45
4	7	80	9.6	55

Safety data

Maximum voltage
Maximum current
Maximum permissible external inductance
Maximum permissible external capacity
Maximum power

$U_o = 18.7 V$

$I_o = 330 mA$

IIC 0.18 mH IIB 1.45 mH


IIC 0.27 μF IIB 1.64 μF

$P_o = 1.42 W$

Application note
For 4-wire circuits (without sense) the respective safety barrier might be unnecessary. The operating data remains unchanged. The safety-relevant maximum current is reduced to $I_o = 310 mA$, the maximum power to $P_o = 1.36 W$.

Thermocouples

Schematic



09958E01

Operating data

Maximum series resistance of the safety barrier
Sensor voltage

$R_{max} = 2 \times 82.1 \Omega$

$U \leq \pm 4 V_{eff} / 6 V_{pp}$

Safety data

Maximum voltage
Maximum current
Maximum permissible external inductance
Maximum permissible external capacity

$U_o = 9.3 V$

$I_o = 300 mA$

IIC 0.2 mH IIB 1.8 mH

IIC 4.1 μF IIB 31 μF

Two-channel safety barriers



Series 9002



Accessories and Spare Parts


Designation	Figure	Description	Art. no.	Weight kg
Back-up fuse	09919E00	for all safety barriers of Series 9001, 9002 and 9004 Packaging unit: 5 pieces	158964	0.008
Label carrier	09920E00		158977	0.002
Labelling sheet	09921E00	perforated, for automatic inscription Format: DIN A4	158973	0.005
Adapter	09922E00		158826	0.006
Clamping base, moulded material	09924E00		165283	0.004
DIN rail	03856E00	NS 35 / 15 (available by the metre)	103714	1.410
Protective conductor terminal	09926E00	USLKG 5 (clamping range ≤ 4 mm²)	112760	0.012
Earthing terminal	09926E00	USLKG 6 N (clamping range ≤ 6 mm²)	112599	0.030
Fuse holder	09927E00		158834	0.020
Insulation and fastening material	09928E00	for mounting rail NS 35/15	158828	0.023

Dimensional Drawings (All Dimensions in mm / inches) - Subject to Alterations




09929E00

Safety barriers 9001, 9002, 9004




09930E00



66 mm
2.60 "

38 mm
1.50 "

09932E00



66 mm
2.60 "

38 mm
1.50 "

09933E00

Safety barrier 9001, 9002, 9004
mounted on the mounting rail LV 35/15

Safety barrier 9001, 9002, 9004
mounted on the mounting rail LV 32
with adaptor and clamping base made of
moulded material

Safety barrier 9001, 9002, 9004
mounted on
mounting plate with adaptor

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice.
The illustrations cannot be considered binding.